



Industrial Grade 21.5" Touch Panel Mount Monitor

1. 1920 x 1080 resolution, 16:9 aspect ratio
2. Multiple signal input VGA + DP + HDMI
3. Front IP65 waterproof and dustproof
4. Aluminum alloy case, better performance of heat dissipation
5. True flat 10 Points P-CAP Touch Screen/ Resistive touch

LCD panel

Panel size	21.5"
Resolution	1920x1080
Aspect ratio	16:9
Support Color	16.7M colors
Brightness (cd/m ²)	300 nits
Contrast ratio	1000:1
Response time	5ms
View angle	89°/89°/89°/89° (R/L/U/D)

Touch panel

Touchscreen Type	10 Points Capacitive Touch
Touch Interface	USB
Touch response time	2ms
Luminousness	90%
Touch options	(5W Resistive touch optional)
Working Life	>50 million times

Power Supply

External Power Supply	AC 100 - 240V , 50-60Hz
Working voltage	DC 12V power input (Wide voltage 12~36V optional)

Technical Doc. :	ST_PTSL215PM-CL_R010.docx
Equipment:	PTSL215PM-CL
Revision :	1.0

Power consumption	35W
Enclosure	
Material	Aluminum Alloy
Color	Black, Silver for choice
VESA mounting	75x75mm/100x100mm
IP-grade	Front panel waterproof IP65
Operating Environment	
Temperature Range	Operating: -10 to 60°C, storage :-20 to 80°C
Relative humidity	5%~95% @ 40° C, non-condensing
Packing Details	
Net weight	6.5KG
Gross weight	8.5KG
Product Dimension	557x345x67.45mm
Packing size	685x460x210mm
Accessories	Power adapter, embedded screws
Other	
Mounting (options)	Wall mounting brackets
	Desk stand holder
Certificates	CE, FCC, RoHs
Warranty	1 year warranty
Signal Ports	
VGA	1xVGA
HDMI	1xHDMI
DVI	1xDVI
Audio In / Out	Yes
OSD	
OSD control	Brightness, contrast ratio, auto adjustment, H/V position, language select etc.
Support languages	English, French, Spanish, Portuguese, Italian, German, Russian, Japanese, Chinese etc.
Support OS	Windows XP , Windows /7/8/10 , Linux, Mac OS X, Android, etc.

Technical Doc. :	ST_PTSL215PM-CL_R010.docx
Equipment:	PTSL215PM-CL
Revision :	1.0

